

Think GAIA
For Life and the Earth

SANYO

LIGHTS UP WITH SOLAR ENERGY

EQUIPPED WITH USB POWER PORT



"Splash proof" water resistance (conforms to JIS IP X 4)

eneloop solar light

SSL-LT1S

Solar light equipped with USB power port

SANYO Electric Co.,Ltd.

SSL-LT1S

Solar light equipped with USB power port



Special Features

- Ideal of outdoors or in the event of emergencies such as natural disaster (without AC power supply)



USB output

- Equipped with a USB output socket^{*1} which can charge mobile phone at times of emergency

- Two types of LED light
 - Panel Light (9 / 5 / 1 LED Light)
 - Beam Light




Panel Light

Beam Light

- SOS signal attached for emergency. Press light switch and USB output button and hold for 4 seconds or longer to generate the SOS signal.

Press both buttons and hold for 4 secs or longer.



- Can be charged from AC Adapter
- Specially designed customized strap which can be attached to the shoulder or tent hooks



Panel Light

^{*1} : External output: Internal battery stores enough energy to charge a mobile phone once (The amount of charging needed varies with the mobile phone models)

Solar Light set includes:

- 1 X Solar Light with USB Power Port
- 1 X AC Adapter
- 1 X Custom Strap

Operating Hours:

Panel Light	9 LED Lights	Approx. 9hrs
	5 LED Lights	Approx. 15hrs
	1 LED Light	Approx. 35hrs
Beam Light		Approx. 50hrs

Charging Time:

Solar Charger	: Approx. 15-30 Daylight hrs Depends on the level of remaining charge and ambient temperature
AC Adapter	: Approx. 3.5hrs
USB Output	: Approx. 110mins

Specification:

Measurement	: L242mm x W186mm x H28mm
Weight	: Approx. 800g
Charger Input	: Solar Charging DC 5.3V 0.45A ^{*1} Via AC Adapter DC5V 1A
Charger Output	: USB Socket DC5V 500mA (max)
AC Adapter Input	: AC 100-240V 50-60Hz
AC Adapter Output	: DC5V 1A

^{*1} Irradiance : 1000 w/m², Module temperature: 25°C

www.eneloop.com.sg